



Instruction:
 1.Type: Film to Glass
 2.Operating Voltage: ≤10V
 3.Response Time: ≤10ms
 4.Storage Temperature: -20℃~+70℃
 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
 6.Hitting Life: >1,000,000 Times ,250gf Force;
 7.writing Life>100,000 Times 250gf Force;
 8.Connect Material: FPC+PIN

9.Film Thickness: 0.188mm
 10.Glass Thickness: 1.8mm
 11.Light transmission: ≥78%
 12.Force: 100g or more
 13.Linearity: ≤5%
 14.Insulation: ≥20MΩ
 15.Resistance: 50Ω<PIN1, PIN2<280Ω
 50Ω<PIN2, PIN4<280Ω
 50Ω<PIN4, PIN5<280Ω
 50Ω<PIN5, PIN1<280Ω
 16.Surface Hardness ≥3H(pencil)

Touch Screen ET-5185A0

REVISIONS						
SCALE	1:1	MATERIAL	F/G		Version	1.0
UNIT	mm	TOLERANCE	±0.3m		NO.	1 of 1
DESIGN	Lany	DATE	20100528	Eagle Touch		
CHECK	Peter • LI	DATE	20100528			
RELEASE	Victor	DATE	20100528			