



Front: ITO Film—0.188mm
 Anti newton ring
 Back Glass—1.8mm

Thick: 2.3 ± 0.15

- Instruction:
- 1.Type: Film to Glass
 - 2.Operating Voltage: $\leq 10V$
 - 3.Response Time: $\leq 10ms$
 - 4.Storage Temperature: $-20^{\circ}C \sim +70^{\circ}C$
 - 5.Operation Temperature/Humidity: $-10^{\circ}C \sim +60^{\circ}C / 20\% \sim 95\%$
 - 6.Hitting Life: $>10,000,000$ Times $250gf$ Force;
 - 7.Writing Life: $>1,000,000$ Times $250gf$ Force;
 - 8.Connect Material: FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission: $\geq 75\%$
- 12.Force: 100g or more
- 13.Linearity: $\leq 5\%$
- 14.Insulation: $\geq 20M \Omega$
- 15.Resistance: $50\Omega < PIN1, PIN2 < 250\Omega$
 $50\Omega < PIN4, PIN5 < 250\Omega$
 $50\Omega < PIN3, PIN6 < 250\Omega$
- 16.Surface Hardness: $\geq 3H$ (pencil)

Touch Screen ET-5200A0

REVISIONS

SCALE	1:1	MATERIAL	F/6	Version	1.0
UNIT	mm	TOLERANCE	$\pm 0.2mm$	NO.:	1 of 1
DESIGN	John	DATE	20090601	Eagle Touch	
CHECK	patricia	DATE	20090601		
RELEASE	J	DATE	20090601		