



- Instruction:
to Glass
- 1.Type:Film to Glass
 - 2.Operating Voltage:≤10V
 - 3.Response Time:≤10ms
 - 4.Storage Temperature: -20℃~+70℃
 - 5.Operation Temperature/Humidity: -10℃~+60℃/ 20%~95%
 - 6.Hitting Life:≥1,000,000 Times 250gf Force;
 - 7.Writing Life:≥1,000,000 Times 250gf Force;
 - 8.Connect Material: FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission: ≥75%
- 12.Force: 100g or more
- 13.Linearity: ≤5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: 50Ω<PIN1, PIN2<250Ω
50Ω<PIN3, PIN4<250Ω
50Ω<PIN5, PIN1<250Ω
- 16.Surface Hardness ≥3H(pencil)

Touch Screen ET-5220A0

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	RELEASED	30Jan	NO.	1 of 1
DESIGN	Jaka	DATE	20090506		
CHECK	peder + J	DATE	20090506		
RELEASE	J	DATE	20090506		

Eagle Touch