



Instruction:

- 1.Type:Film to Glass
- 2.Operating Voltage:≤10V
- 3.Response Time:≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life:>1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times 250gf Force;
- 8.Connect Material:FPC

- 9.Film Thickness:0.188mm
- 10.Glass Thickness:1.1mm
- 11.Light transmission: ≥78%
- 12.Force:100g or more
- 13.Linearity:≤1.5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: X: 520Ω~900Ω
Y: 180Ω~330Ω
- 16.Surface Hardness ≥3H(pencil)

REVISIONS

| SCALE | 1:1 | MATERIAL | F/G | Version | 1.0 |
|---------|----------|-----------|----------|---------|--------|
| UNIT | mm | TOLERANCE | ±0.3mm | NO. | 1 of 1 |
| DESIGN | Lucy | DATE | 20090505 | | |
| CHECK | Peter LI | DATE | 20090505 | | |
| RELEASE | Victor | DATE | 20090505 | | |