



Instruction:

- 1.Type:Film to Glass
- 2.Operating Voltage: ≤10V
- 3.Response Time: ≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life:>10,000,000 Times ,250gf Force;
- 7.writing Life>1,000,000 Times 250gf Force;
- 8.Connect Material:FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.1mm
- 11.Light transmission: ≥78%
- 12.Force: 100g or more
- 13.Linearity: ≤5%
- 14.Insulation: ≥20M Ω
- 15.Resistance: 50Ω < PIN1, PIN2 < 250Ω
50Ω < PIN2, PIN4 < 250Ω
50Ω < PIN4, PIN5 < 250Ω
50Ω < PIN5, PIN1 < 250Ω
- 16.Surface Hardness ≥3H(pencil)

Thick: 1.4 ± 0.15

Eagle Touch

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	±0.3m	NO.	1 of 1
DESIGN	Jaka	DATE	20090610		
CHECK	petar • II	DATE	20090611		
RELEASE	J	DATE	20090612		