



**Instruction:**

- 1.Type: Film to Glass
- 2.Operating Voltage:  $\leq 10V$
- 3.Response Time:  $\leq 10ms$
- 4.Storage Temperature:  $-20^{\circ}\sim+70^{\circ}$
- 5.Operation Temperature/Humidity :  $-10^{\circ}\sim+60^{\circ}/ 20\%\sim95\%$
- 6.Hitting Life:  $>1,000,000$  Times ,250gf Force;
- 7.writing Life $>100,000$  Times 250gf Force;
- 8.Connect Material:FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission:  $\geq 78\%$
- 12.Force: 100g or more
- 13.Linearity:  $\leq 5\%$
- 14.Insulation:  $\geq 20M\Omega$
- 15.Resistance:
  - $50\Omega < PIN1, PIN2 < 280\Omega$
  - $50\Omega < PIN3, PIN4 < 280\Omega$
  - $50\Omega < PIN5, PIN6 < 280\Omega$
- 16.Surface Hardness  $\geq 3H$ (pencil)

**REVISIONS**

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	$\pm 0.3m$	NO.	1 of 1
DESIGN	Lucy	DATE	20100519		
CHECK	Peter • L.	DATE	20100519		
RELEASE	Victor	DATE	20100519		