



Front: ITO Film-0.188mm
 Anti newton ring
 Back Glass-1.8mm

- Instruction:
- Type: Film to Glass
 - Operating Voltage: $\leq 10V$
 - Response Time: $\leq 10ms$
 - Storage Temperature: $-20^{\circ}C \sim +70^{\circ}C$
 - Operation Temperature/Humidity: $-10^{\circ}C \sim +60^{\circ}C / 20\% \sim 95\%$
 - Hitting Life: $> 10,000,000$ Times ,250gf Force;
 - writing Life $> 1,000,000$ Times 250gf Force;
 - Connect Material: FPC+PIN
 - Film Thickness: 0.188mm
 - Glass Thickness: 1.8mm
 - Light transmission: $\geq 78\%$
 - Force: 100g or more
 - Linearity: $\leq 5\%$
 - Insulation: $\geq 20M \Omega$
 - Resistance: $50 \Omega < PIN1, PIN2 < 250 \Omega$
 $50 \Omega < PIN2, PIN4 < 250 \Omega$
 $50 \Omega < PIN4, PIN5 < 250 \Omega$
 $50 \Omega < PIN5, PIN1 < 250 \Omega$
 - Surface Hardness $\geq 3H$ (pencil)

Touch Screen ET-5170A0

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	$\pm 0.3m$	NO.:	1 of 1
DESIGN	Jaka	DATE	20090505	Eagle Touch	
CHECK	petar • 11	DATE	20090505		
RELEASE	J	DATE	20090505		