


- Instruction:
- 1.Type: Film to Glass
  - 2.Operating Voltage: ≤10V
  - 3.Response Time: ≤10ms
  - 4.Storage Temperature: -20℃~+70℃
  - 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
  - 6.Hitting Life: >1,000,000 Times ,250gf Force;
  - 7.writing Life:>1,000,000 Times 250gf Force;
  - 8.Connect Material: FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission: ≥73%
- 12.Force: 100g or more
- 13.Linearity: ≤5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: 50Ω<P1M1, P1M2<250Ω  
50Ω<P1M4, P1M5<250Ω  
50Ω<P1M3, P1M6<250Ω
- 16.Surface Hardness: ≥3H(pencil)

Front ITO Film 0.188mm  
hard coating anti newton ring  
Back Glass—1.8mm

总厚度: 2.3 ± 0.15



### Touch Screen ET-5191A0

#### REVISIONS

SCALE	1:1	MATERIAL	F/0	Version	1.0
UNIT	mm	TOLERANCE	±0.3mm	MA: 1 of 1	
DESIGN	Jaka	DATE	20090506		
CHECK	patric	DATE	20090506		
RELEASE	J	DATE	20090506		

Eagle Touch