



4 由 Autodesk 教育版产品制作

4 由 Autodesk 教育版产品制作

- Instruction:
- 1.Type:Film to Glass
  - 2.Operating Voltage:≤10V
  - 3.Response Time:≤10ms
  - 4.Storage Temperature: -20℃~+70℃
  - 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
  - 6.Hitting Life:≥1,000,000 Times ,250gf Force;
  - 7.writing Life:≥100,000 Times 250gf Force;
  - 8.Connect Material:FPC

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 0.7mm
- 11.Light transmission: ≥78%
- 12.Force:100g or more
- 13.Linearity:≤1.5%
- 14.Insulation: ≥20M Ω
- 15.Resistance: X: 500 Ω~1000 Ω;  
Y: 170 Ω~330 Ω
- 16.Surface Hardness: ≥3H(pencil)

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version
UNIT	mm	TOLERANCE	±0.3mm	NO.
DESIGN	Lucy	DATE	20090826	1 of 1
CHECK	Lucy	DATE	20090826	
RELEASE	Viewer	DATE	20090826	

G F E D C B A