



- Instruction:
- 1.Type: Film to Glass
 - 2.Operating Voltage: DCSV 1mA
 - 3.Response Time: $S.30ms$
 - 4.Storage Temperature: $-30^{\circ}C \sim +80^{\circ}C$
 - 5.Operation Temperature/Humidity: $-20^{\circ}C \sim +70^{\circ}C / 20\% \sim 95\%$
 - 6.Hitting Life: $>1,000,000$ Times $\sim 250gf$ Force;
 - 7.writing Life: $>100,000$ Times $250gf$ Force;
 - 8.Connect Material: FPC

- 9.Film Thickness: $0.188mm$
- 10.Glass Thickness: $1.1mm$
- 11.Light transmission: $\geq 78\%$
- 12.Force: $\leq 20g \sim 150g$
- 13.Linearity: $\leq 1.5\%$
- 14.Resistance: $\geq 20M \Omega$ ($0.005V$)
- 15.Resistance: Y: $100 \Omega \sim 450 \Omega$, X: $200 \Omega \sim 700 \Omega$
- 16.Surface Hardness: $\geq 3H$ (pencil)

REVISIONS			
NO	DATE	DESCRIPTION	BY
1	20090820	1:1	Ver: 1.0
2	20090820	Layer	1 of 1
3	20090820	Pinout	
4	20090820	View	