



Front ITO film 0.188mm
hard coating anti newton ring

Back ITO glass 1.1mm

Thick: 1.4 ±0.15

Instruction:

- 1.Type: Film to Glass
- 2.Operating Voltage: ≤10V
- 3.Response Time: ≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life: >1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times 250gf Force;
- 8.Connect Material: FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.1mm
- 11.Light transmission: ≥75%
- 12.Force: 100g or more
- 13.Linearity: ≤1.5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: X: 410Ω~800Ω
Y: 200Ω~410Ω
- 16.Surface Hardness ≥3H(pencil)

REVISIONS						
SCALE	1:1	MATERIAL	F/G		Version	1.0
UNIT	mm	TOLERANCE	±0.3mm		NO.	1 of 1
DESIGN	Lucy	DATE	20091029			
CHECK	Peter • LI	DATE	20091029			
RELEASE	Victor	DATE	20091029			