



Instruction:
 1.Type:Film to Glass
 2.Operating Voltage: ≤10V
 3.Response Time: ≤10ms
 4.Storage Temperature: -20℃~+70℃
 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
 6.Hitting Life:>1,000,000 Times ,250gf Force;
 7.writing Life>100,000 Times 250gf Force;
 8.Connect Material:FPC

9.Film Thickness: 0.188mm
 10.Glass Thickness: 1.1(1.8)mm
 11.Light transmission: ≥78%
 12.Force: 100g or more
 13.Linearity: ≤1.5%
 14.Insulation: ≥20MΩ
 15.Resistance: X: $\begin{matrix} \ominus & \ominus \\ \sim & \sim \end{matrix}$
 Y: $\begin{matrix} \ominus & \ominus \\ \sim & \sim \end{matrix}$
 16.Surface Hardness ≥3H(pencil)

REVISIONS						
SCALE	1:1	MATERIAL	F/G		Version	1.0
UNIT	mm	TOLERANCE	±0.3mm		NO	1 of 1
DESIGN	Lucy	DATE	20110116			
CHECK	Peter • Li	DATE	20110216			
RELEASE	Victor	DATE	20110216			