



Instruction:

- Type: Film to Film
- Operating Voltage:  $\leq 10V$
- Response Time:  $\leq 10ms$
- Storage Temperature:  $-20^{\circ}C \sim +70^{\circ}C$
- Operation Temperature/Humidity:  $-10^{\circ}C \sim +60^{\circ}C$  /  $20\% \sim 95\%$
- Hitting Life:  $> 10,000,000$  Times,  $250gf$  Force;
- Writing Life:  $> 1,000,000$  Times  $250gf$  Force;
- Connect Material: FPC+PIN

- Film Thickness:  $0.188mm$
- Thickness:  $1.1mm$
- Light transmission:  $\geq 78\%$
- Force:  $100g$  or more
- Linearity:  $\leq 1.5\%$
- Insulation:  $\geq 20M \Omega$
- Resistance:  $50 \Omega < PIN1, PIN2 < 250 \Omega$   
 $50 \Omega < PIN3, PIN4 < 250 \Omega$   
 $50 \Omega < PIN5, PIN6 < 250 \Omega$
- Surface Hardness  $\geq 3H$  (pencil)

REVISIONS

SCALE	1:1	MATERIAL	F/F	Version
UNIT	MM	TOLERANCE	$\pm 0.3mm$	NO.: 1 of 1
DESIGN	Jshiba	DATE	20090717	
CHECK	pasaka	DATE	20090717	
RELEASE	J	DATE	20090717	